

BEL-AIR Heavy-duty Carrying Cases




STANDARD HARDWARE

Shell: High-density Polyethylene **Hinge:** 4" x 1 7/8" Steel Hinge



Valance: 2" Aluminum Valance



Latch: Steel Twist Draw Latch




Handle: Steel Spring-loaded Handle



Lid Stay: 9" Heavy-duty Lid Stay **O-Ring:** Neoprene Gasket

OPTIONAL HARDWARE



- Stainless steel padlock hasp
- Stainless steel latch protector
- Built-in key lock
- Pressure relief valve
- Telescoping handle
- Built-in rigid wheels
- Removeable casters
- Label and card holders
- Humidity indicator

All dims are approximate inside dims in inches.



Heights shown are the minimum and maximum heights possible for the case lid and base respectively. Not all lid and base combinations are possible.

Standard Hardware Configuration ->

* = horizontal ribs
= shell w/o ribs

Weight (lbs.)
(approximate at tallest height)

H L H
a a t
n d c
l h g
e e s
s s s

Length	Width	Total Height	Lid Height	Base Height	Case I.D.#	Weight (lbs.)	H	L	H
8	6 1/2	4 to 7	2 to 3 1/2	2 to 3 1/2	MS0806	4	1	1	2 1
9	9	5 to 12	2 1/2 to 6	2 1/2 to 6	MS0909	5	1	1	2 1
11	4	3 to 6	1 1/2 to 3	1 1/2 to 3	MS1104#	4	1	2	2 1
11	7	4 to 9	2 to 4 1/2	2 to 4 1/2	MS1107#	5	1	2	2 1
10 3/4	8	4 to 9	2 to 4 1/2	2 to 4 1/2	MS1108*	5	1	2	2 1
12	9	5 to 10	2 1/2 to 5	2 1/2 to 5	MS1209	6	1	2	2 1
12	10	4 to 6	2 to 3	2 to 3	MS1210#	6	1	2	2 1
12	12	4 to 9	2 to 4 1/2	2 to 4 1/2	MS1212#S	7	1	2	2 1
12	12	7 to 13 1/2	2 to 4 1/2	5 to 9	MS1212#M	8	1	2	2 1
12	12	10 to 18	5 to 9	5 to 9	MS1212#D	10	1	2	2 1
14	8	4 to 9	2 to 4 1/2	2 to 4 1/2	MS1408#	7	1	2	2 1
14	10	5 to 9	2 1/2 to 4 1/2	2 1/2 to 4 1/2	MS1410*S	8	1	2	2 1
14	10	8 to 13 1/2	2 1/2 to 4 1/2	5 1/2 to 9	MS1410*M	9	1	2	2 1
14	10	11 to 18	5 1/2 to 9	5 1/2 to 9	MS1410*D	10	1	2	2 1
15	10	7 to 8	3 1/2 to 4	3 1/2 to 4	MS1510	8	1	2	2 1
15	11	5 to 8 1/2	2 1/2 to 3 1/2	2 1/2 to 5	MS1511	9	1	2	2 1
16	6 1/2	5 to 9	2 1/2 to 4 1/2	2 1/2 to 4 1/2	MS1606	6	1	2	2 1
16	10	5 to 9	2 1/2 to 4 1/2	2 1/2 to 4 1/2	MS1610	7	1	2	2 1
16	11 1/2	9 to 18	4 1/2 to 8 1/2	4 1/2 to 9 1/2	MS1612D	10	1	2	2 1
15 1/4	13 1/4	5 to 7	2 1/2 to 3 1/2	2 1/2 to 3 1/2	MS1614S	10	1	2	2 1

All dims are approximate inside dims in inches.



Heights shown are the minimum and maximum heights possible for the case lid and base respectively. Not all lid and base combinations are possible.

Standard Hardware Configuration ->

* = horizontal ribs
= shell w/o ribs

Weight (lbs.)
(approximate at tallest height)

H L A H
a n t i
d c n t
e s e s
S
t
a
y
s

Length	Width	Total Height	Lid Height	Base Height	Case I.D.#	Weight (lbs.) (approximate at tallest height)	H	L	A	H
15 1/4	13 1/4	10 to 13	2 1/2 to 3 1/2	7 1/2 to 9 1/2	MS1614M	11	1	2	2	1
15 1/4	13 1/4	15 to 19	7 1/2 to 9 1/2	7 1/2 to 9 1/2	MS1614D	12	1	2	2	1
17	10 3/4	5 to 9	2 1/2 to 4 1/2	2 1/2 to 4 1/2	MS1710	8	1	2	2	1
17	11	4 to 6	2 to 3	2 to 3	MS1711#	8	1	2	2	1
17	12 3/4	4 to 9	2 to 4 1/2	2 to 4 1/2	MS1712*	9	1	2	2	1
17	15	7 to 13	3 1/2 to 6 1/2	3 1/2 to 6 1/2	MS1715	10	1	2	2	1
18	10	5 to 16	2 1/2 to 8	2 1/2 to 8	MS1810	9	1	2	2	1
18	10 1/2	5 to 12	2 1/2 to 6	2 1/2 to 6	MS1810*	8	1	2	2	1
17 1/2	12 1/2	6 to 13 1/2	3 to 6	3 to 7 1/2	MS1813S	10	1	2	2	1
17 1/2	12 1/2	11 to 17	3 to 6	8 to 11	MS1813M	11	1	2	2	1
17 3/4	13 3/4	7 to 11	3 1/2 to 5 1/2	3 1/2 to 5 1/2	MS1814*	11	1	2	2	1
17 1/2	17 1/2	6 to 12	3 to 6	3 to 6	MS1818#	12	1	2	2	1
19	5	4 to 8	2 to 4	2 to 4	MS1905#	9	1	2	2	1
19	12 1/4	5 to 15	2 1/2 to 7 1/2	2 1/2 to 7 1/2	MS1912*	11	1	2	2	1
20	6	5 to 9	2 1/2 to 4 1/2	2 1/2 to 4 1/2	MS2006	9	1	2	2	2
20	11 3/4	6 to 11	3 to 5 1/2	3 to 5 1/2	MS2012*	11	1	2	2	2
20	14	4 to 12	2 to 6	2 to 6	MS2014	12	1	2	2	2
20 3/4	14 1/4	5 to 12 1/2	2 1/2 to 6 1/4	2 1/2 to 6 1/4	MS2014*	12	1	2	2	2
20	16	7 to 14	3 1/2 to 7	3 1/2 to 7	MS2016	13	1	2	2	2
20	16	6 to 13	3 to 6 1/2	3 to 6 1/2	MS2016*	13	1	2	2	2
21	7	4 to 7	2 to 3	2 to 4	MS2107	10	1	2	2	2
21	10	4 to 10	2 to 5	2 to 5	MS2110#S	11	1	2	2	2
21	10	9 to 15	2 to 5	7 to 10	MS2110#M	12	1	2	2	2
21	10	14 to 20	7 to 10	7 to 10	MS2110#D	13	1	2	2	2
21	13	7 to 13	3 1/2 to 6 1/2	3 1/2 to 6 1/2	MS2113	13	1	2	2	2
21	14	6 to 16	3 to 8	3 to 8	MS2114	13	1	2	2	2
21	17	6 to 12	3 to 6	3 to 6	MS2117	14	1	2	2	2
22	8	6 to 24	3 to 12	3 to 12	MS2208D	20	1	2	2	2
22	16	6 to 9	3 to 4 1/2	3 to 4 1/2	MS2216S	14	1	2	2	2
22	16	8 1/2 to 12 1/2	3 to 4 1/2	5 1/2 to 8	MS2216M	15	1	2	2	2
22	16	11 to 16	5 1/2 to 8	5 1/2 to 8	MS2216D	16	1	2	2	2
22	18 1/4	6 to 12 1/2	3 to 6 1/4	3 to 6 1/4	MS2218*	16	1	2	2	2
22	18	6 to 9	3 to 4 1/2	3 to 4 1/2	MS2218S	15	1	2	2	2

All dims are approximate inside dims in inches.



Heights shown are the minimum and maximum heights possible for the case lid and base respectively. Not all lid and base combinations are possible.

Standard Hardware Configuration ->

* = horizontal ribs
= shell w/o ribs

Weight (lbs.)
(approximate at tallest height)

H L A H
a n d l e s
i n c h e s
t a n g e s
S t a y s

Length	Width	Total Height	Lid Height	Base Height	Case I.D.#	Weight (lbs.) (approximate at tallest height)	H	L	A	H
22	18	10 to 16 1/2	3 to 4 1/2	7 to 12	MS2218M	16	1	2	2	2
22	18	14 to 24	7 to 12	7 to 12	MS2218D	17	1	2	2	2
22	22	7 to 15	3 1/2 to 7 1/2	3 1/2 to 7 1/2	MS2222	19	1	2	2	2
23	8	6 to 9	3 to 4 1/2	3 to 4 1/2	MS2308	11	1	2	2	2
23	10	5 to 6	2 1/2 to 3	2 1/2 to 3	MS2310S	12	1	2	2	2
23	10	8 1/2 to 12	2 1/2 to 3	6 to 9	MS2310M	13	1	2	2	2
23	10	12 to 18	6 to 9	6 to 9	MS2310D	14	1	2	2	2
22 1/2	14 1/4	7 to 13	3 1/2 to 6 1/2	3 1/2 to 6 1/2	MS2314*	14	1	2	2	2
23	22	5 to 10	2 1/2 to 5	2 1/2 to 5	MS2322	18	1	2	2	2
24	10	4 to 7	2 to 2 1/2	2 to 4 1/2	MS2410#	14	1	2	2	2
24	13	6 to 13	3 to 6 1/2	3 to 6 1/2	MS2413	13	1	2	2	2
24	16	4 to 10	2 to 5	2 to 5	MS2416#	14	1	2	2	2
24	19	7 to 14	3 1/2 to 7	3 1/2 to 7	MS2419S	15	1	2	2	2
24	19	11 1/2 to 19	3 1/2 to 7	8 to 12	MS2419M	16	1	2	2	2
24	19	16 to 24	8 to 12	8 to 12	MS2419D	17	1	2	2	2
24	20	4 to 18	2 to 9	2 to 9	MS2420D	17	1	2	2	2
24	24	8 to 24	4 to 12	4 to 12	MS2424D	18	1	4	2	2
25	15	8 to 14	4 to 7	4 to 7	MS2515	14	1	2	2	2
25	16	8 to 14	4 to 7	4 to 7	MS2516	14	1	2	2	2
25 1/4	18 1/4	8 to 13	4 to 6 1/2	4 to 6 1/2	MS2518*	15	1	2	2	2
25	25	8 to 26	4 to 13	4 to 13	MS2525D	20	1	4	2	2
26	7	6 to 12	3 to 6	3 to 6	MS2607	13	1	2	2	2
26	12	6 to 16	3 to 8	3 to 8	MS2612	15	1	2	2	2
26	14	4 to 6	2 to 3	2 to 3	MS2614#	14	1	2	2	2
26	16	7 1/2 to 12	2 1/2 to 4	5 to 8	MS2616M	15	1	2	2	2
26	24	4 to 10	2 to 5	2 to 5	MS2624#	19	1	4	2	2
26	26	8 to 19	4 to 9 1/2	4 to 9 1/2	MS2626D	23	1	4	2	2
27	13	5 to 10	2 1/2 to 5	2 1/2 to 5	MS2713	18	1	2	2	2
27	20	7 to 11	3 1/2 to 5 1/2	3 1/2 to 5 1/2	MS2720	20	1	2	2	2
28	14	7 to 13	3 1/2 to 6 1/2	3 1/2 to 6 1/2	MS2814	17	1	2	2	2
28	17 1/2	7 to 10	3 1/2 to 5	3 1/2 to 5	MS2818S	20	1	2	2	2
28	17 1/2	9 1/2 to 14	3 1/2 to 5	6 to 9	MS2818M	21	1	2	2	2
28	17 1/2	12 to 18	6 to 9	6 to 9	MS2818D	22	1	2	2	2

All dims are approximate inside dims in inches.



Heights shown are the minimum and maximum heights possible for the case lid and base respectively. Not all lid and base combinations are possible.

Standard Hardware Configuration ->

* = horizontal ribs
= shell w/o ribs

Weight (lbs.)
(approximate at tallest height)

H L A H
a n d l e s
i n c h e s
t a l l e s t
h e i g h t
s

Length	Width	Total Height	Lid Height	Base Height	Case I.D.#	Weight (lbs.) (approximate at tallest height)	H	L	A	H
28	20	7 to 10	3 1/2 to 5	3 1/2 to 5	MS2820	18	1	2	2	2
28	22	7 to 12	3 1/2 to 6	3 1/2 to 6	MS2822	20	1	2	2	2
29	18 1/2	8 to 12	4 to 6	4 to 6	MS2919S	20	1	2	2	2
29	18 1/2	12 to 18	4 to 6	8 to 12	MS2919M	22	1	2	2	2
29	18 1/2	16 to 24	8 to 12	8 to 12	MS2919D	24	1	2	2	2
30	10	4 to 8	2 to 3 1/2	2 to 4 1/2	MS3010#	15	1	2	2	2
30	25	8 to 26	4 to 13	4 to 13	MS3025D	28	1	4	2	2
30	30	6 to 16	3 to 8	3 to 8	MS3030	26	1	4	2	2
31	11	5 to 8	2 1/2 to 4	2 1/2 to 4	MS3111S	16	1	2	2	2
31	11	7 1/2 to 16	2 1/2 to 4	5 to 12	MS3111M	18	1	2	2	2
31	11	10 to 24	5 to 12	5 to 12	MS3111D	20	1	2	2	2
31	15 1/2	7 to 12	3 1/2 to 6	3 1/2 to 6	MS3115	18	1	2	2	2
31	22	7 to 15	3 1/2 to 7 1/2	3 1/2 to 7 1/2	MS3122	24	1	2	2	2
31	29	7 to 14	3 1/2 to 7	3 1/2 to 7	MS3129	27	1	4	2	2
32	14 1/2	7 to 23	3 1/2 to 11 1/2	3 1/2 to 11 1/2	MS3214D	18	1	2	3	2
33	13	4 to 12	2 to 6	2 to 6	MS3313	18	1	2	3	2
34	18	6 to 8	3 to 4	3 to 4	MS3418S	21	1	2	3	2
34	18	9 to 12	3 to 4	6 to 8	MS3418M	23	1	2	3	2
34	18	12 to 16	6 to 8	6 to 8	MS3418D	25	1	2	3	2
35	8	7 to 12	3 1/2 to 6	3 1/2 to 6	MS3508	17	1	2	3	2
36	31 1/2	10 to 25	5 to 12.5	5 to 12.5	MS3632D	32	1	4	3	2
37	12	4 to 8	2 to 4	2 to 4	MS3712#	21	1	2	3	2
37 1/2	19 1/2	6 to 13	3 to 6 1/2	3 to 6 1/2	MS3719S	25	1	2	3	2
37 1/2	19 1/2	11 to 18 1/2	3 to 6 1/2	8 to 12	MS3719M	27	1	2	3	2
37 1/2	19 1/2	16 to 24	8 to 12	8 to 12	MS3719D	29	1	2	3	2
38	9	8 to 14	4 to 7	4 to 7	MS3809	20	1	2	3	2
39	17	5 to 6	2 1/2 to 3	2 1/2 to 3	MS3917S	23	1	4	3	2
39	17	7 1/2 to 10 1/2	2 1/2 to 3	5 to 7 1/2	MS3917M	25	1	4	3	2
39	17	10 to 15	5 to 7 1/2	5 to 7 1/2	MS3917D	27	1	4	3	2
40	8	6 to 12	3 to 6	3 to 6	MS4008	20	1	4	4	2
40	18	8 to 16	4 to 8	4 to 8	MS4018	28	1	4	4	2
40	22	8 to 16	4 to 8	4 to 8	MS4022	30	1	4	4	2
42	16	6 to 8	3 to 4	3 to 4	MS4216	28	1	4	4	2

All dims are approximate inside dims in inches.



Heights shown are the minimum and maximum heights possible for the case lid and base respectively. Not all lid and base combinations are possible.

Standard Hardware Configuration ->

* = horizontal ribs
= shell w/o ribs

Weight (lbs.)
(approximate at tallest height)

**H L
a a
n t
d c
l h
e e
s s**
**H i
n t
g a
y s**

Length	Width	Total Height	Lid Height	Base Height	Case I.D.#	Weight (lbs.)	H	L	H	S
44	8	6 to 12	3 to 6	3 to 6	MS4408	22	1	4	4	2
44	12	6 to 16	3 to 8	3 to 8	MS4412	28	1	4	4	2
44	15	5 to 8	2 1/2 to 4	2 1/2 to 4	MS4415S	28	1	4	4	2
44	15	8 1/2 to 19	2 1/2 to 4	6 to 15	MS4415M	30	1	4	4	2
44	15	12 to 30	6 to 15	6 to 15	MS4415D	32	1	4	4	2
46	13	5 to 8	2 1/2 to 4	2 1/2 to 4	MS4613	26	1	4	4	2
48	14	8 to 14	4 to 7	4 to 7	MS4814	28	1	4	4	2
48	24	8 to 16	4 to 8	4 to 8	MS4824	32	1	6	4	2
54	16 1/2	8 to 13	4 to 6 1/2	4 to 6 1/2	MS5416	30	1	4	5	2
54	20	8 to 13	4 to 6 1/2	4 to 6 1/2	MS5420	34	1	4	5	2
58	20	7 to 12	3 1/2 to 6	3 1/2 to 6	MS5820S	36	1	4	6	2
58	20	14 to 22	3 1/2 to 6	10 1/2 to 16	MS5820M	39	1	4	6	2
58	20	21 to 32	10 1/2 to 16	10 1/2 to 16	MS5820D	42	1	4	6	2