

BEL-AIR Heavy Duty Shipping Cases




STANDARD HARDWARE

Shell: High-density Polyethylene **Hinge:** 4" x 1 7/8" Steel Hinge



Valance: 2" Aluminum Valance



Latch: Steel Twist Draw Latch




Handle: Steel Spring-loaded Handle



Lid Stay: 9" Heavy-duty Lid Stay

O-Ring: Neoprene Gasket

OPTIONAL HARDWARE



- Stainless steel padlock hasp
- Stainless steel latch protector
- Built-in key lock
- Pressure relief valve
- Telescoping handle
- Built-in rigid wheels
- Removeable casters
- Label and card holders
- Humidity indicator

All dims are approximate inside dims in inches.



Heights shown are the minimum and maximum heights possible for the case lid and base respectively. Not all lid and base combinations are possible.

Standard Hardware Configuration ->

H L A H S
a a n t i
d c n g e
s s e s

Weight (lbs.)
(approximate at tallest height)

Length	Width	Total Height	Lid Height	Base Height	Case I.D.#	Weight (lbs.) (approximate at tallest height)	H	L	A	H	S
12	12	9 to 14	4 1/2 to 7	4 1/2 to 7	AP1212S	9	1	2	2	1	
12	12	12 1/2 to 18	4 1/2 to 7	8 to 11	AP1212M	10	2	2	2	1	
12	12	16 to 22	8 to 11	8 to 11	AP1212D	11	2	2	2	1	
15	12	10 to 16	5 to 8	5 to 8	AP1512S	11	1	2	2	1	
16	16	8 to 15	4 to 7 1/2	4 to 7 1/2	AP1616S	12	1	2	2	1	
16	16	13 1/2 to 20	4 to 7 1/2	9 1/2 to 12 1/2	AP1616M	13	2	2	2	1	
16	16	19 to 25	9 1/2 to 12 1/2	9 1/2 to 12 1/2	AP1616D	14	2	2	2	1	
18	14 1/2	8 to 14	4 to 7	4 to 7	AP1814S	12	1	2	2	1	
18	14 1/2	12 to 21	4 to 7	8 to 14	AP1814M	13	2	2	2	1	
18	14 1/2	16 to 28	8 to 14	8 to 14	AP1814D	16	2	2	2	1	
19	10	10 to 11	5 to 5 1/2	5 to 5 1/2	AP1910S	11	1	2	2	1	
19	10	15 1/2 to 16	5 to 5 1/2	11 to 11 1/2	AP1910M	12	2	2	2	1	
19	10	22 to 23	11 to 11 1/2	11 to 11 1/2	AP1910D	13	2	2	2	1	
21	12	9 to 12	4 1/2 to 6	4 1/2 to 6	AP2112S	13	1	2	2	2	
21	12	14 1/2 to 17 1/2	4 1/2 to 6	10 to 11 1/2	AP2112M	14	2	2	2	2	
21	12	20 to 23	10 to 11 1/2	10 to 11 1/2	AP2112D	15	2	2	2	2	
22	18	6 to 13	3 to 6 1/2	3 to 6 1/2	AP2218S	15	1	2	2	2	
22	18	11 1/2 to 16 1/2	3 to 6 1/2	8 1/2 to 10	AP2218M	17	3	2	2	2	
22	18	17 to 20	8 1/2 to 10	8 1/2 to 10	AP2218D	19	3	2	2	2	
24	24	11 to 14	5 1/2 to 7	5 1/2 to 7	AP2424S	20	1	4	2	2	
24	24	16 to 19 1/2	5 1/2 to 7	10 1/2 to 12 1/2	AP2424M	22	5	4	2	2	

All dims are approximate inside dims in inches.



Heights shown are the minimum and maximum heights possible for the case lid and base respectively. Not all lid and base combinations are possible.

Standard Hardware Configuration ->

Weight (lbs.)
(approximate at tallest height)

H
a
n
d
l
e
s

L
a
t
t
h
e
s

H
i
g
h
t
s

S
t
a
y
s

Length	Width	Total Height	Lid Height	Base Height	Case I.D.#	Weight (lbs.) (approximate at tallest height)	H a n d l e s	L a t t h e s	H i g h t s	S t a y s
24	24	21 to 25	10 1/2 to 12 1/2	10 1/2 to 12 1/2	AP2424D	24	5	4	2	2
25 1/2	21	12 to 15	6 to 7 1/2	6 to 7 1/2	AP2521S	18	1	2	2	2
25 1/2	21	16 to 19 1/2	6 to 7 1/2	10 to 12	AP2521M	20	3	2	2	2
25 1/2	21	20 to 24	10 to 12	10 to 12	AP2521D	22	3	2	2	2
27	12 1/2	7 to 8 1/2	3 1/2 to 4 1/2	3 1/2 to 4 1/2	AP2712S	14	1	2	2	2
27	12 1/2	10 1/2 to 12	3 1/2 to 4 1/2	7 to 7 1/2	AP2712M	17	3	2	2	2
27	12 1/2	14 to 15	7 to 7 1/2	7 to 7 1/2	AP2712D	20	3	2	2	2
27	27	14 to 21	7 to 10 1/2	7 to 10 1/2	AP2727D	28	5	4	2	2
28	18	11 to 15	5 1/2 to 7 1/2	5 1/2 to 7 1/2	AP2818S	20	1	2	2	2
28	18	14 to 17 1/2	5 1/2 to 7 1/2	8 1/2 to 10	AP2818M	22	3	2	2	2
28	18	17 to 20	8 1/2 to 10	8 1/2 to 10	AP2818D	24	3	2	2	2
27 1/2	25	13 to 15	6 1/2 to 7 1/2	6 1/2 to 7 1/2	AP2825S	26	5	4	2	2
27 1/2	25	17 to 23	6 1/2 to 7 1/2	10 1/2 to 15 1/2	AP2825M	29	5	4	2	2
27 1/2	25	21 to 31	10 1/2 to 15 1/2	10 1/2 to 15 1/2	AP2825D	32	5	4	2	2
30	12	9 to 12	4 1/2 to 6	4 1/2 to 6	AP3012S	16	1	2	2	2
30	12	14 1/2 to 18	4 1/2 to 6	10 to 12	AP3012M	18	3	2	2	2
30	12	20 to 24	10 to 12	10 to 12	AP3012D	20	3	2	2	2
30	18	17 to 22	8 1/2 to 11	8 1/2 to 11	AP3018D	24	3	2	2	2
31	20	9 to 16	4 1/2 to 8	4 1/2 to 8	AP3120S	26	3	2	2	2
31	22	10 to 14	5 to 7	5 to 7	AP3122S	27	3	2	2	2
31	22	15 to 19	5 to 7	10 to 12	AP3122M	29	3	2	2	2
31	22	20 to 24	10 to 12	10 to 12	AP3122D	32	3	2	2	2
32	14	12 to 16	6 to 8	6 to 8	AP3214S	24	3	2	2	2
32	14	14 to 18	6 to 8	8 to 10	AP3214M	26	3	2	2	2
32	14	16 to 20	8 to 10	8 to 10	AP3214D	28	3	2	2	2
34	17	14 to 17	7 to 8 1/2	7 to 8 1/2	AP3418S	30	3	4	3	2
34	24	6 to 21	3 to 10 1/2	3 to 10 1/2	AP3424S	35	5	4	3	2
34	24	14 1/2 to 24 1/2	3 to 10 1/2	11 1/2 to 14	AP3424M	38	5	4	3	2
34	24	23 to 28	11 1/2 to 14	11 1/2 to 14	AP3424D	41	5	4	3	2
36	20	20 to 24	10 to 12	10 to 12	AP3620D	36	3	4	3	2
43	25	8 to 16	4 to 8	4 to 8	AP4325S	42	5	4	4	2
43	25	16 1/2 to 21 1/2	4 to 8	12 1/2 to 13 1/2	AP4325M	45	5	4	4	2
43	25	25 to 27	12 1/2 to 13 1/2	12 1/2 to 13 1/2	AP4325D	48	5	4	4	2
48	24	21 to 27	10 1/2 to 13 1/2	10 1/2 to 13 1/2	AP4824D	54	5	4	4	2